

# Kabelverschraubungen / Cable Glands

**we**ge® S Standard UD-VITON

<b>Material</b>	Edelstahl 1.4571	<b>material</b>	stainless steel AISI 316 Ti
<b>Dichteinsatz</b>	VITON	<b>sealing insert</b>	VITON
<b>O-Ring</b>	VITON	<b>o-ring</b>	VITON
<b>Schutzklasse</b>	IP66/ IP68 - 5 bar	<b>protection class</b>	IP66/ IP68 - 5 bar
<b>Zugentlastung</b>	DIN EN 62444 Tab. 2A	<b>strain relief</b>	DIN EN 62444 Tab. 2A
<b>Temperaturbereich</b>	-25 °C bis +230 °C	<b>range of temperature</b>	-25 °C to +230 °C

Gewinde thread			H	L		Bestell-Nr. ref.-number
-------------------	--	--	---	---	--	----------------------------

kurzes Anschlussgewinde / short connection thread						
M 12 x 1,5	2,5 – 5	14	22	5	50	391.1200.2
M 12 x 1,5	5 – 7	14	22	5	50	391.1200.1
M 16 x 1,5	3 – 5	17	24	5,5	50	391.1600.2
M 16 x 1,5	5 – 7	17	24	5,5	50	391.1600.0
M 16 x 1,5	7 – 9	17	24	5,5	50	391.1600.4
M 16 x 1,5	8 – 10	17	24	5,5	50	391.1600.1
M 20 x 1,5	4 – 8	22	27	6	50	391.2000.3
M 20 x 1,5	7 – 10	22	27	6	50	391.2000.0
M 20 x 1,5	10 – 12	22	27	6	50	391.2000.2
M 20 x 1,5	11 – 14	22	27	6	50	391.2000.1
M 25 x 1,5	11 – 14	30	31	7	25	391.2500.0
M 25 x 1,5	15 – 19	30	31	7	25	391.2500.1
M 32 x 1,5	15 – 18	34	32	8	25	391.3200.0
M 32 x 1,5	19 – 22	34	32	8	25	391.3200.1
M 40 x 1,5	21 – 24	44	39	8	10	391.4000.0
M 40 x 1,5	25 – 28	44	39	8	10	391.4000.1

