



E-STREAM

E-Stream GmbH & Co. KGaA

Am Ringofen 26

41189 Mönchengladbach

Germany

Fact sheet

ES18650-32LP

Lithium-Ion 18650 rechargeable battery cell

**Nominal specifications**

Note: The present specification refers exclusively to single cells.

Performance at pack level may differ.

Capacity	Nominal 3100mAh	At 0.2C discharge to 2.5V and 0.2C charge to 4.2V
	Minimum 2950mAh	
Nominal voltage [V]	3.65	
Energy [Wh]	11.315	
Discharge cut-off voltage [V]	2.5	
Maximum charge voltage [V]	4.2	
Internal Impedance ACIR [mΩ]	≤ 30	
Standard charge current [A]	1.55	0.5C
Standard charge cut-off current [mA]	155	0.05C
Maximum continuous charge current [A]*	2.17	0.7C
Standard discharge current [A]	2.85	1C
Maximum continuous discharge current [A]**	9.3	3C
Weight [g]	≤ 47	
Diameter [mm]	18.25 ± 0.2	
Height [mm]	64.95 ± 0.2	
Operating temperatures charge [°C]	0 ≤ T ≤ 50	
Operating temperatures discharge [°C]	-20 ≤ T ≤ 55	
Cut-off temperature limit discharge [°C]	55	
Cycle life (80% of initial capacity)	≥ 1000 cycles (standard charge/discharge)	
Storage temperatures with maximum 70% relative humidity	≤ 30 days	-20°C – 60°C
	> 30 ≤ 90 days	-20°C – 45°C
	> 90 ≤ 365 days	-20°C – 25°C

*Not for cycle life

**With 55°C temperature cut



Appearance



Revision History

Version	Created by	Date of approval	Changes
v1.0	Nils Erdmann	11/10/2020	Initial

Author	Date and signature	Approval	Date and signature
Jamshid Tavana		Nils Erdmann	